



TERMS OF USE OF VENEER FLOORING VENIFLOOR IN FINISHING UV VARNISH + CORUNDUM

Venifloor is a top class product produced by ZIP LLC. It is made of natural raw materials and is characterized by high usable and aesthetic quality.

Store the floors in the original cardboard boxes before laying.

1. Floors can not be stored outdoors or in a damp place where they can be soaked. Under no circumstances should floors be installed that contain any damage (e.g. broken quick release lock, no veneer in the top layer, etc.).

2. The temperature of use of veneer floors in the room should be within the range from 18 to 27 degrees C.

3. Relative humidity in a room should be between 45 and 60%.

4. Care: The frequency of floor care should be adequate to the degree of use of boards in normal operating conditions.

4.1. First care: Boards should be cleaned with a wooden floor care agent in a varnished finish immediately after laying.

4.2. Daily care: The frequency of floor care should be adequate to the degree of its use under normal operating conditions.

4.3. Periodic care: It should be performed every 3 months or every 6 months. It should be used with Intensive concentrated cleaner and Emulsion.

*The list of recommended preparations and the manner of their use are available on the website www.venifloor.com in the "Maintenance" - "Care of varnished floors".

5. Under no circumstances should you leave wet traces on the floor after cleaning. Damage to the floor caused by water or other liquids is not a basis for complaints.

6. Under no circumstances should the veneer floor be covered with PE foil or other materials that do not let air and moisture.

7. To remove dust from the floor surface soft, dry or slightly damp cloths should be used. The sand or gravel applied to the floor surface should be removed immediately as it causes scratches on the surface layer of wood and varnish as well as minor dents. Damage caused by the application of sand is not covered by the warranty.

8. Mechanical damages resulting from use are not covered by the warranty.

9. Under the elements of interior furnishings (such as furniture, armchairs, chairs with wheels, etc.) having direct contact with the floor, appropriate protective materials should be placed, e.g. felt pads or rugs, which protect the floor against mechanical damage. Wipers should be placed near the door. Small stones that remain on the soles of the shoes may cause minor scratches, so it is important to wipe the shoes before installing the wiper on the floor.

10. Renewal: Renovation of the varnish layer after many years of using the floor is done by sanding the wear layer (varnish) and then by applying a new layer of varnish. A similar system has in its offer, among others Bona. The option of renewing the floor after the creation of deep, mechanical damage is their regeneration through the use of the so-called. hot hard waxes that perfectly - in a permanent and practically indistinguishable way in terms of color - fill larger losses. More information is available on the website www.venifloor.com in the "Renovation" - "Renovation of varnished floors".

11. The user is required to familiarize the cleaning staff with the above-described conditions of use of veneered floors Venifloor in the finish varnish UV + CORUNDUM.

The manufacturer provides a guarantee when using laid floors in accordance with its guidelines.

I confirm that you have read the guidelines and warranty conditions above.

.....

Date, address, legible signature of the user